

Alfaflat M



Very light and easy to handle lay flat water hose. Is suitable for the supply of water without or under minimal pressure. Perfect on the outlet of pumps on construction sites (open end), but also often used as protection on cables, hydraulic hoses, stowage,...

Temperature: -10°C to +60°C

Construction: plastified blue pvc that is extruded round a polyester reinforcement, is resistant to some chemical products and atmospheric influences

Wall thickness is bigger then with the L-version.

Assembly

can be assembled with all industrial couplings, normally attached by hose clamps

Reference	Diameter (mm)	Diameter flat (mm)	Weight (g/m)	Coil length (m)
MM020	20	31	150	50
MM025	25	39	170	50 - 100
MM030	30	47	200	50
MM032	32	50	220	50 - 100
MM035	35	55	240	50
MM038	38	60	300	50 - 100
MM040	40	63	320	50 - 100
MM045	45	71	350	50
MM050	50	78	390	50 - 100
MM055	55	86	460	50
MM063	63	99	510	50
MM070	70	110	550	50 - 100
MM075	75	118	600	50
MM080	80	126	650	50
MM090	90	141	730	50 - 100
MM100	100	157	900	50
MM110	110	173	1000	50
MM125	125	196	1100	50
MM150	150	236	1480	50
MM200	200	314	2400	50
MM250	250	393		50