

Alfavac Grijs



Very flexible grey pvc hose for suction and conveying air or fumes. Can be grounded by means of both steel ends.

Construction: grey pvc and embedded steel spiral with white cover

Temperature: -10°C to +65°C

Applications

Because of his enorm flexibility this tube is recommended to the aeration of ateliers, machines, and to eliminate smoke etc.

Reference	Diameter (mm)	Wire (mm)	Wall thickness (mm)	Weight (g/m)	Bending radius (mm)	Vacuum (mH20)	Coil length (m)
VFG030	30	1 x 1,5	0,8	250	30	4	10
VFG035	35	1 x 1,5	0,8	260	35	4	10
VFG040	40	1 x 1,5	0,8	300	40	4	10
VFG045	45	1 x 1,5	0,8	320	45	4	10
VFG050	50	1,5 x 1,9	0,8	380	50	3	10
VFG055	55	1,5 x 1,9	0,8	400	55	3	10
VFG060	60	1,5 x 1,9	0,8	450	60	3	10
VFG065	65	1,5 x 1,9	0,8	500	65	3	10
VFG070	70	1,5 x 1,9	0,8	520	70	3	10
VFG075	75	1,5 x 1,9	0,8	550	75	2	10
VFG080	80	1,5 x 1,9	0,8	630	80	2	10
VFG090	90	1,5 x 1,9	0,8	700	90	2	10
VFG100	100	1,8 x 2,2	0,8	740	100	2	10
VFG110	110	1,8 x 2,2	0,8	790	110	2	10
VFG120	120	1,8 x 2,2	0,8	850	120	2	10
VFG125	125	1,8 x 2,2	0,8	880	125	2	10
VFG130	130	1,8 x 2,2	0,8	890	130	1	10
VFG140	140	1,8 x 2,2	0,8	910	140	1	10
VFG150	150	1,8 x 2,2	0,8	950	150	1	10
VFG160	160	1,8 x 2,2	1	1000	160	1	10
VFG180	180	1,8 x 2,2	1	1300	180	1	10
VFG200	200	1,8 x 2,2	1	2050	200	1	10
VFG250	250	2,2 x 2,7	1	2850	250	1	10
VFG300	300	2,2 x 2,7	1	3650	300	1	10

Product ID: 14160

Source URL: <https://www.alfaflex.be/en/products/10000/14000/alfavac-grijs-0>