



## ASFA-L

ASFA-L worm-drive clips are very compact, but are also of outstanding quality. The smooth band underside and beveled band edges assure that the hose doesn't get damaged while or after mounting.

Following DIN 3017 and available in W2 and W4 version.

Bandwidth: 9mm

**W2:** zinc-plated screw with stainless steel (AISI-430) band and housing

**W4:** screw, band and housing in stainless steel (AISI-304)

### Applications

**W2:** very suitable for standard domestic or professional applications

**W4:** suitable for standard applications with possible corrosion

| Ø min - max<br>(mm) | Max torque<br>(Nm) | Box qty<br>(pc) | Ref W2 | Ref W4 |
|---------------------|--------------------|-----------------|--------|--------|
| 8 - 16              | 3,0                | 200             | KAS08  | KASI08 |
| 12 - 22             | 3,0                | 200             | KAS12  | KASI12 |
| 16 - 27             | 3,5                | 200             | KAS16  | KASI16 |
| 20 - 32             | 3,5                | 200             | KAS20  | KASI20 |
| 25 - 40             | 4,0                | 100             | KAS25  | KASI25 |
| 30 - 45             | 4,0                | 100             | KAS30  | -      |
| 32 - 50             | 4,0                | 100             | KAS32  | KASI32 |
| 40 - 60             | 4,0                | 100             | KAS40  | KASI40 |
| 50 - 70             | 4,0                | 100             | KAS50  | -      |
| 60 - 80             | 4,0                | 100             | KAS60  | KASI60 |
| 70 - 90             | 4,0                | 50              | KAS70  | KASI70 |
| 80 - 100            | 4,0                | 50              | KAS80  | -      |

Product ID: 122010

Source URL: <https://www.alfaflex.be/en/products/120000/asfa-l-0>